





Introducing the masky C400 commercial prints chine: — this arrordable and stylish chiller is the perfect choice for any business. With its white exterior, the Husky C400 blends seamlessly with any setting, adding a touch of sophistication to your business space. Its stylish design enhances the overall ambiance, making it an attractive centrepiece. Featuring a generous 397-litre capacity, the Husky C400 provides ample space to accommodate a wide variety of beverages. With its five sturdy

## Glass Door Upright Fridge

## **Product features**

- 397-litre storage capacity
- Double-glazed door
- Wide temperature range

## **Design and Material**

HandleIntegralShelves Number & Type5 wire white + baseFeet2 adjustable feet / 4 rollersExterior ColourWhiteInterior LightYesLockNoCooling and FunctionsTemperature Range°C+2 to +8Climate Class3Type of ControllerMechanicalType of CoolingVentilatedType of DefrostAutomaticRefrigerantR600aRefrigerant Chargeg70SuitabilityCommercialPower and ConsumptionBeverage CoolerEnergy ClassDEnergy ConsumptionkWh/24h2.30Annual Energy ConsumptionkWh/year839PlugUKInput PowerW408Voltage / FrequencyV/Hz220-240/50Weight and DimensionsGross / Net Weightkg95 / 80CapacityI397Internal Dimension (HxWxD)mm1365 x 530 x 580External Dimension (HxWxD)mm2135 x 660 x 700Packed Dimension (HxWxD)mm2213 x 702 x 78240ft HC Container Loadpcs51	Door Number & Type		1 hinged glass door
Feet 2 adjustable feet / 4 rollers  Exterior Colour White  Interior Light Yes  Lock No  Cooling and Functions  Temperature Range °C +2 to +8  Climate Class 3  Type of Controller Mechanical  Type of Cooling Ventilated  Type of Defrost Automatic  Refrigerant R600a  Refrigerant Charge g 70  Suitability Commercial  Power and Consumption  Product Classification Beverage Cooler  Energy Class D  Energy Consumption kWh/year 839  Plug UK  Input Power W 408  Voltage / Frequency V/Hz 220-240/50  Weight and Dimensions  Gross / Net Weight kg 95 / 80  Capacity I 397  Internal Dimension (HxWxD) mm 1365 x 530 x 580  External Dimension (HxWxD) mm 2213 x 660 x 700  Packed Dimension (HxWxD) mm 2213 x 660 x 700  Packed Dimension (HxWxD) mm 2213 x 702 x 782	Handle		Integral
Exterior Colour  Interior Light  Lock  No  Cooling and Functions  Temperature Range  Colimate Class  Type of Controller  Type of Cooling  Ventilated  Type of Defrost  Refrigerant  Refooda  Refrigerant Charge  Suitability  Commercial  Power and Consumption  Product Classification  Beverage Cooler  Energy Class  Energy Consumption  Refrigery Consumption  Plug  UK  Input Power  Woltage / Frequency  V/Hz  Voltage / Frequency  V/Hz  Voltage / Frequency  V/Hz  Capacity  Internal Dimension (HxWxD)  Mm  Packed Dimension (HxWxD)  Molecular Average  No  Commercial  Commercial  Beverage Cooler  Beverage C	Shelves Number & Type		5 wire white + base
Interior Light  Lock  No  Cooling and Functions  Temperature Range  °C  +2 to +8  Climate Class  3  Type of Controller  Mechanical  Type of Cooling  Ventilated  Type of Defrost  Automatic  Refrigerant  Refrigerant  Refrigerant Charge  9  70  Suitability  Commercial  Power and Consumption  Product Classification  Beverage Cooler  Energy Class  D  Energy Consumption  Annual Energy Consumption  Plug  UK  Input Power  W  408  Voltage / Frequency  V/Hz  220-240/50  Weight and Dimensions  Gross / Net Weight  kg  95 / 80  Capacity  Internal Dimension (HxWxD)  mm  1365 x 530 x 580  External Dimension (HxWxD)  Packed Dimension (HxWxD)  mm  2213 x 702 x 782	Feet		2 adjustable feet / 4 rollers
Lock No  Cooling and Functions  Temperature Range °C +2 to +8  Climate Class 3  Type of Controller Mechanical  Type of Cooling Ventilated  Type of Defrost Automatic  Refrigerant R600a  Refrigerant Charge 9 70  Suitability Commercial  Power and Consumption  Product Classification Beverage Cooler  Energy Class D  Energy Consumption kWh/24h 2.30  Annual Energy Consumption kWh/year 839  Plug UK  Input Power W 408  Voltage / Frequency V/Hz 220-240/50  Weight and Dimensions  Gross / Net Weight kg 95 / 80  Capacity I 397  Internal Dimension (HxWxD) mm 1365 x 530 x 580  External Dimension (HxWxD) mm 2213 x 702 x 782	Exterior Colour		White
Cooling and Functions         Temperature Range       °C       +2 to +8         Climate Class       3         Type of Controller       Mechanical         Type of Cooling       Ventilated         Type of Defrost       Automatic         Refrigerant       R600a         Refrigerant Charge       g       70         Suitability       Commercial         Power and Consumption       Beverage Cooler         Energy Class       D         Energy Consumption       kWh/24h       2.30         Annual Energy Consumption       kWh/year       839         Plug       UK         Input Power       W       408         Voltage / Frequency       V/Hz       220-240/50         Weight and Dimensions       Gross / Net Weight       kg       95 / 80         Capacity       I       397         Internal Dimension (HxWxD)       mm       1365 x 530 x 580         External Dimension (HxWxD)       mm       2135 x 660 x 700         Packed Dimension (HxWxD)       mm       2213 x 702 x 782	Interior Light		Yes
Temperature Range °C +2 to +8  Climate Class 3  Type of Controller Mechanical  Type of Cooling Ventilated  Type of Defrost Automatic  Refrigerant R600a  Refrigerant Charge 9 70  Suitability Commercial  Power and Consumption  Product Classification Beverage Cooler  Energy Class D  Energy Consumption kWh/24h 2.30  Annual Energy Consumption kWh/year 839  Plug UK  Input Power W 408  Voltage / Frequency V/Hz 220-240/50  Weight and Dimensions  Gross / Net Weight kg 95/80  Capacity I 397  Internal Dimension (HxWxD) mm 1365 x 530 x 580  External Dimension (HxWxD) mm 2135 x 660 x 700  Packed Dimension (HxWxD) mm 2213 x 702 x 782	Lock		No
Climate Class Type of Controller Mechanical Type of Cooling Ventilated Type of Defrost Automatic Refrigerant Refooa Refrigerant Charge Guitability Commercial Power and Consumption Product Classification Beverage Cooler Energy Class D Energy Consumption kWh/24h 2.30 Annual Energy Consumption Refrigerant Refooa Refrigerant Charge Guitability Commercial Refrigerant Charge Guitability Guitab	<b>Cooling and Functions</b>		
Type of Controller Type of Cooling Ventilated Type of Defrost Refrigerant Refrigerant Refrigerant Charge Guitability Commercial Power and Consumption Product Classification Beverage Cooler Energy Class D Energy Consumption kWh/24h 2.30 Annual Energy Consumption kWh/year Refrigerant Charge UK Input Power V 408 Voltage / Frequency V/Hz 220-240/50 Weight and Dimensions Gross / Net Weight kg 95 / 80 Capacity Internal Dimension (HxWxD) mm 1365 x 530 x 580 External Dimension (HxWxD) Packed Dimension (HxWxD) mm 2213 x 702 x 782	Temperature Range	°C	+2 to +8
Type of Cooling  Type of Defrost  Refrigerant  Refrigerant  Refrigerant Charge  Suitability  Commercial  Power and Consumption  Product Classification  Energy Class  D  Energy Consumption  Annual Energy Consumption  Plug  UK  Input Power  W  408  Voltage / Frequency  V/Hz  220-240/50  Weight and Dimensions  Gross / Net Weight  kg  95 / 80  Capacity  Internal Dimension (HxWxD)  mm  1365 x 530 x 580  External Dimension (HxWxD)  Packed Dimension (HxWxD)  mm  2213 x 702 x 782	Climate Class		3
Type of Defrost  Refrigerant Refrigerant Charge  Suitability Commercial  Power and Consumption  Product Classification Beverage Cooler Energy Class D Energy Consumption  Refrigerant Refrigerant Charge  Product Classification Reverage Cooler Energy Class D Energy Consumption Refrigerant Refrigerant Charge Refrigerant Charge Refrigerant Refri	Type of Controller		Mechanical
Refrigerant         R600a           Refrigerant Charge         g         70           Suitability         Commercial           Power and Consumption           Product Classification         Beverage Cooler           Energy Class         D           Energy Consumption         kWh/24h         2.30           Annual Energy Consumption         kWh/year         839           Plug         UK         UK           Input Power         W         408           Voltage / Frequency         V/Hz         220-240/50           Weight and Dimensions         Gross / Net Weight         kg         95 / 80           Capacity         I         397           Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Type of Cooling		Ventilated
Refrigerant Charge         g         70           Suitability         Commercial           Power and Consumption           Product Classification         Beverage Cooler           Energy Class         D           Energy Consumption         kWh/24h         2.30           Annual Energy Consumption         kWh/year         839           Plug         UK         Input Power         W         408           Voltage / Frequency         V/Hz         220-240/50           Weight and Dimensions           Gross / Net Weight         kg         95 / 80           Capacity         I         397           Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Type of Defrost		Automatic
Suitability Commercial  Power and Consumption  Product Classification Beverage Cooler  Energy Class D  Energy Consumption kWh/24h 2.30  Annual Energy Consumption kWh/year 839  Plug UK  Input Power W 408  Voltage / Frequency V/Hz 220-240/50  Weight and Dimensions  Gross / Net Weight kg 95 / 80  Capacity I 397  Internal Dimension (HxWxD) mm 1365 x 530 x 580  External Dimension (HxWxD) mm 2135 x 660 x 700  Packed Dimension (HxWxD) mm 22135 x 660 x 700	Refrigerant		R600a
Power and Consumption           Product Classification         Beverage Cooler           Energy Class         D           Energy Consumption         kWh/24h         2.30           Annual Energy Consumption         kWh/year         839           Plug         UK           Input Power         W         408           Voltage / Frequency         V/Hz         220-240/50           Weight and Dimensions         kg         95 / 80           Capacity         I         397           Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Refrigerant Charge	9	70
Product Classification         Beverage Cooler           Energy Class         D           Energy Consumption         kWh/24h         2.30           Annual Energy Consumption         kWh/year         839           Plug         UK           Input Power         W         408           Voltage / Frequency         V/Hz         220-240/50           Weight and Dimensions         Gross / Net Weight         kg         95 / 80           Capacity         I         397           Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Suitability		Commercial
Energy Class         D           Energy Consumption         kWh/24h         2.30           Annual Energy Consumption         kWh/year         839           Plug         UK           Input Power         W         408           Voltage / Frequency         V/Hz         220-240/50           Weight and Dimensions         Gross / Net Weight         kg         95 / 80           Capacity         I         397           Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Power and Consumption	n	
Energy Consumption         kWh/24h         2.30           Annual Energy Consumption         kWh/year         839           Plug         UK           Input Power         W         408           Voltage / Frequency         V/Hz         220-240/50           Weight and Dimensions         Gross / Net Weight         kg         95 / 80           Capacity         I         397           Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Product Classification		Beverage Cooler
Annual Energy Consumption         kWh/year         839           Plug         UK           Input Power         W         408           Voltage / Frequency         V/Hz         220-240/50           Weight and Dimensions         Gross / Net Weight         kg         95 / 80           Capacity         I         397           Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Energy Class		D
Plug         UK           Input Power         W         408           Voltage / Frequency         V/Hz         220-240/50           Weight and Dimensions           Gross / Net Weight         kg         95 / 80           Capacity         I         397           Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Energy Consumption	kWh/24h	2.30
Input Power         W         408           Voltage / Frequency         V/Hz         220-240/50           Weight and Dimensions           Gross / Net Weight         kg         95 / 80           Capacity         I         397           Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Annual Energy Consumption	kWh/year	839
Voltage / Frequency         V/Hz         220-240/50           Weight and Dimensions           Gross / Net Weight         kg         95 / 80           Capacity         1         397           Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Plug		UK
Weight and Dimensions           Gross / Net Weight         kg         95 / 80           Capacity         1         397           Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Input Power	W	408
Gross / Net Weight         kg         95 / 80           Capacity         I         397           Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Voltage / Frequency	V/Hz	220-240/50
Capacity         397           Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Weight and Dimensions	;	
Internal Dimension (HxWxD)         mm         1365 x 530 x 580           External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Gross / Net Weight	kg	95 / 80
External Dimension (HxWxD)         mm         2135 x 660 x 700           Packed Dimension (HxWxD)         mm         2213 x 702 x 782	Capacity	1	397
Packed Dimension (HxWxD) mm 2213 x 702 x 782	Internal Dimension (HxWxD)	mm	1365 x 530 x 580
	External Dimension (HxWxD)	mm	2135 x 660 x 700
40ft HC Container Load pcs 51	Packed Dimension (HxWxD)	mm	2213 x 702 x 782
	40ft HC Container Load	pcs	51

Husky Refrigerators (UK) Ltd. 37 Station Road, Lutterworth, Leicestershire LE17 4AP, U.K.